

UTP Category 6 Cables (0.50mm)

CAB-LC3100B-E2-IN



Specifications

Model	CAB-LC3100B-E2-IN
Cable	
Product model	CAB-LC3100B-E2-IN
Product specification	HSYV-6 4×2×0.50
Test Standard	Fluke Test 90m
Packing length	305±1 m
Rip-cord	Yes
Seperator	Yes
Ambient temperature	-20°C~75°C
Conductor	
Material	Solid-Bare Copper
AWG	24
Nom.O.D.(mm)	0.50±0.01 mm
DC resistance	≤95 Ω/km
Insulation	
Material	HDPE
Diameter	0.90±0.05 mm
Color	Blue/White- Blue,Green/White-Green,Orange/White-Orange,Brown/White-Brown
Sheath	
Material	PVC
External O.D.	5.6±0.3 mm
Thickness	0.55±0.1 mm

Color	Orange
Tensile strength	>13.8 Mpa
Surface Printing	
Letter height	3.0±0.3 mm
Print error / Space	1±0.005 m
Color	Black
Packing	
Packing	Pallet
Once packing dimension	420mm*205mm*420mm

Ordering Info

Product Model	Description
CAB-LC3100B-E2-IN	Cat6(UTP),305m,BC,Orange

Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.